

DT-1126

Diesel Applicator Spray (DAPS)

Diesel Applicator Spray

Product Information

Produktinformation



Product properties:

Diesel Applicator Spray for cleaning of the air intake of diesel engines. Even highly adhesive and heavy deposits will be removed without residue. In this case, the complete valve and intake system, especially inlet valves, piston rings, top land and the entire combustion chamber will not only be cleaned but also lubricated and protected.



Area of application

Service product for use in diesel powered engines. Recommended for engines with particulate filter, turbo and catalytic converter.



Application

Do not fill in to the diesel tank. Spray while the engine running into the air intake system of the diesel engine. If the engine runs smoothly, spray the product constantly in the air intake pipe, in rough engine running in short bursts.



Consumption

300ml sufficient for 1-2 applications



Reaction time

approx. 20 seconds



Technical data

Physical state: aerosol
Colour: clear/colourless
Odour: aromatic
Flashpoint: < 0 °C
Ignition temperature: > 200 °C
Density at 68 °F: 0.815-0.825 g/cm³
Water resistant



Available size

1L 5L 10L 25L 200L



Diatec International GmbH
Neuköllner Str 203 - 12357 Berlin
Email : info@dticc.com
Website : www.dticc.com

TEL: 0049177588641 / 00493098539728

DIATEC[®]

Our information is based on careful examination and may be considered as reliable. However, all information supplied is a non-binding advise. No liability for printing errors, technical modifications and errors excepted.

 Made in Germany