

DT - 5026

Radiator Conditioner (RC)

Radiator Conditioner



Product properties:

Diatec radiator conditioner protects against rust and corrosion, prevents electrolysis and cavitation, lubricates valves, thermostats and water pumps, heat exchangers and improves the heat exchange of liquid, maintains the ph value and prevents deposits of limestone in the cooling system. A longer life of the units and an increased operational reliability will be achieved.



application Area

Suitable for all closed cooling systems. Radiator is miscible with all commercially available antifreeze.



Application

Regularly admit the cooling system at each interval of service prescribed by the manufacturer. For additional or reduced quantities per liter coolant increase or reduce the addition of Radiator conditioner to 50 ml. Prescribed use of this product no coolant change is necessary. Caution! It is miscible with all commercially available antifreeze radiator conditioner.



Consumption

300 ml for passenger cars (sufficient for cooling systems of 5-10 litres capacity) Mix ratio 1:20



Reaction time

While engine is running



Technical data

Physical state: liquid
Colour: clear/colourless
Odour: odourless
pH-Value (at 68 °F): 9 - 10
Ignition temperature: > 400 °C
Density at 68 °F: 1,09 g/cm³
Water soluble



Available size

300 ml

1L 5L 10L 25L 200L

Product Information

Produktinformation



Diatec International GmbH
Neuköllner Str 203 - 12357 Berlin
Email : info@dticc.com

Website : www.dticc.com
TEL: 0049177588641 / 00493098539728

DIATEC®

Our information is based on careful examination and may be considered as reliable. However, all information supplied is a non-binding advise. No liability for printing errors, technical modifications and errors excepted.



Made in Germany