

DT - 5036

Radiator Stop Leak (RSL)

Radiator Stop Leak



Product properties:

Diatec Radiator Stop Leak reliable seals leaky water coolers and heat exchangers, leaking water pumps and valves, loose connections and cracked coolant hoses without clogging the system. The use of Diatec Radiator Stop Leak increase the reliability and lifetime of the engine. Finally, the environmental impact is reduced through dense cooler. Diatec Radiator Stop Leak is also ideally suitable for preventive applications.

Product Information

Produktinformation



application Area Usage in all units and systems with closed water cooling circuit



Application Admit Diatec Radiator Stop Leak to the coolant and set the heater to heat. After that check the sealing coolant level. Contains no toxic or irritant substances.



Consumption Kühlsystem-dicht
300 ml sufficient for 5 - 10 liters of cooling water.
Mix Ratio 1:20



Reaction time Radiator Stop Leak
While engine is running



Technical data Physical state: liquid
Colour: green
Odour: noticeable
Initial boiling point and boiling range: 85 - 110 °C
Density at 68 °F: 0,95 - 1,1 g/cm³
Water soluble



Available size 300 ml
1L 5L 10L 25L 200L

Diatec International GmbH
Neuköllner Str 203 - 12357 Berlin Email : info@dticc.com
Website : www.dticc.com
TEL: 0049177588641 / 00493098539728

DIATEC[®]

Our information is based on careful examination and may be considered as reliable. However, all information supplied is a non-binding advise. No liability for printing errors, technical modifications and errors excepted.



Made in Germany