

DT - 2056

Easy Gear (EG)

Easy Gear



Product properties:

The highly effective anti-friction barrier seals all the internal surfaces of engines and equipment. Remarkably reduces wear and tear and guarantees optimized lubrication throughout the temperature range. Keeps seals, shaft seals and "o" rings soft and supple. Easy Gear ensures smooth gear changing and quieter operation. Improves the temperature bandwidth and helps to prevent oxidation of the gear oil.



application Area

In all manual gearboxes, secondary and differential transmissions. Do not use in automatic transmissions and gearboxes with wet clutches



Application

Add to the gear oil. Use with every oil change or the used oil (observe the maximum filling quantity, reduce the oil quantity if necessary). The product is miscible with all commercially available oils. Observe the mixing ratio!



Consumption

300 ml for 2-3 ltr. gear oil. Mixing Ratio 1:60



Reaction time

Works during operation



Technical data

Physical state: viscous
Colour: brown
Odour: mild
Flashpoint: > 100 °C
Density at 68 °F: 0.89 - 0.92 g/cm³
Water resistant



Available size

1L 5L 10L 25L 200L



Product Information

Produktinformation



Diatec International GmbH
Neuköllner Str 203 - 12357 Berlin
TEL: 0049177588641 / 00493098539728
Website: www.dticc.com
Email: info@dticc.com

DIATEC®

Our information is based on careful examination and may be considered as reliable. However, all information supplied is a non-binding advise. No liability for printing errors, technical modifications and errors excepted.



Made in Germany