

DT - 3066

Octane Premium

Octane Premium



Product properties

With the TÜV-certified Octane Premium, based on the newest additive technology, the RON octane number of the fuel is increased by up to 6 points. For this reason, Octane Premium is ideally suited for use in lower quality fuels. Even during low output conditions the combustion, antiknock quality and response of the engine is significantly improved. Regular use keeps the fuel system clean (Keep-Clean-Effect).



Application Area

For use in the fuel system of petrol engines.



Application

Fill directly into the petrol tank. Observe mixing ratio.



Consumption

300 ml treats up to 80 liters of fuel. Mix ratio 1:200



Reaction time

While engine is running



Technical data

Physical state: liquid
Colour: reddish brown
Odour: characteristic
Flashpoint: 24 °C
Density at 59 °F: 0,87 - 0,89 g/cm³
Water resistant



Available size

300 ml
1L 5L 10L 25L 200L

Product Information Produktinformation



Diatec International GmbH
Neuköllner Str 203 - 12357 Berlin
Email : info@dticc.com
Website : www.dticc.com
TEL: 0049177588641 / 00493098539728

DIATEC®

Our information is based on careful examination and may be considered as reliable. However, all information supplied is a non-binding advise. No liability for printing errors, technical modifications and errors excepted.