

DT-1176

DPF Top Gun Cleaner (DPF-TGC)

DPF Top Gun Cleaner

Product Information

Produktinformation



Product properties:

Diesel Particulate Filter Cleaner solves and removes all soot deposition and residues without disassembly. DPF Top Gun Cleaner cleans gently and can be used on all aluminum, magnesium, zinc and cadmium parts. The product can be used perfectly for the latest generation of particulate filters.



Area of application Suitable for all diesel particulate filters.

Allow the exhaust system to cool to ambient temperature. Check for any leaks and verify that the emission system is functioning correctly. Pour the cleaner into the device and attach to a compressed air source. Pressure should be between 2,5–4.0 bar (Adjustment of the air pressure via the scaled rotary wheels on the device). Dismantle the temperature and /or pressure sensor on the diesel particulate filter and insert the probe through the opening (Spraying the liquid through one opening is sufficient, a greater effectiveness can be achieved by additional spraying of the liquid through the second opening). At intervals (spraying 5 seconds/stop 5 seconds) spray the product into the diesel particle filter using the special probe (Engine is not running). We recommend 500 ml of cleaning fluid should be used. But this is dependent on the degree of contamination in the diesel particulate filter. The application can be repeated if required. During the cleaning the deposits are dissolved and are then simply removed from the exhaust system under normal driving conditions. The product is non-flammable. After the cleaning process reinstall all the sensors. Perform a test drive of at least 20 minutes and perform regeneration of the DPF.



Application

Depended on contamination



Consumption



Reaction time

Works during application



Technical data

Physical state: liquid
Colour: clear/colourless
Odour: characteristic
pH-Value (at 68 °F): 10 - 11,5
Melting point: > 0 °C
Initial boiling point and boiling range: > 98 °C
Flashpoint: > 65 °C
Density at 68 °F: 0,99 - 1,1 g/cm³
Water solubility: miscible
Viscosity / kinematic (at 104 °F): ~1,0 mm²/s



Available size

300 ml

1L 5L 10L 25L 200L



DIATEC

Diatec International GmbH
Neuköllner Str 203 - 12357 Berlin
Email : info@dticc.com
Website : www.dticc.com
TEL: 0049177588641 / 00493098539728

Our information is based on careful examination and may be considered as reliable. However, all information supplied is a non-binding advise. No liability for printing errors, technical modifications and errors excepted.



Made in Germany