

DT - 2036

Automatic Transmission Conditioner (ATC) Produktinformation



Product properties:

Automatic Transmission Conditioner reduces friction, facilitates the shifting process and supports the maintenance of seals and sealing rings. This results in smoother shifting and longer shelf life. The re-deposition of resins and similar contaminants is retarded, the oxidation is slowed, the heat loss is reduced, and optimum lubrication is ensured. This results in improved performance, extended oil change intervals and lower operating and maintenance costs.



application Area

For all converter and CVT transmissions as well as automatic gearboxes without wet clutch.



Application

Add Automatic Transmission Protection to gear oil. Do not exceed the maximum filling level. If necessary, reduce the oil quantity. Observe the mixing ratio!



Consumption

300 ml sufficient for 1 vehicle, Mixing Ratio 1:10



Reaction time

works during operation



Technical data

Physical state: viscous
Colour: red
Odour: mild
Flashpoint: > 100 °C
Density at 68 °F: 0.87 - 0.92 g/cm³
Water resistant
Viscosity / kinematic (at 104 °F): 45,9 mm²/s



Available size

1L 5L 10L 25L 200L



Diatec International GmbH
Neuköllner Str 203 - 12357 Berlin
Email : info@dticc.com
Website : www.dticc.com
TEL: 0049177588641 / 00493098539728

DIATEC®

Our information is based on careful examination and may be considered as reliable. However, all information supplied is a non-binding advise. No liability for printing errors, technical modifications and errors excepted.



Made in Germany