

DT - 2066

Gear Oil Stop Leak (GOSL)

Gear Oil Stop Leak



Product properties:

Gear Oil Stop Leak reliably stops the oil loss on the seals of manual gearboxes. Protects gearbox against lack of lubrication and damage due to oil loss. Reduces wear and tear and ensures optimum lubrication. Maintains seals, O-rings and shaft-seals and keeps them supple. Reduces the oxidation of transmission oils.



application Area

In all manual gearboxes, secondary and differential transmissions. **Do not use in automatic transmissions and gearboxes with wet clutches.**



Application

Add to the gear oil. Use with every oil change or the used oil (observe the max. filling quantity, reduce the oil quantity if necessary). The product is miscible with all commercially available oils. Observe the mixing ratio!



Consumption

300 ml for 2-3 ltr. gear oil. Mixing Ratio 1:60



Reaction time

Works during running.



Technical data

Physical state: viscous
Colour: brown
Odour: mild
Flashpoint: > 100 °C
Density at 68 °F: 0.89 - 0.92 g/cm³
Water resistant



Available size

1L 5L 10L 25L 200L



Product Information

Produktinformation



Diatec International GmbH
Neuköllner Str 203 - 12357 Berlin
Email : info@dticc.com
Website : www.dticc.com
TEL: 0049177588641 / 00493098539728

DIATEC®

Our information is based on careful examination and may be considered as reliable. However, all information supplied is a non-binding advise. No liability for printing errors, technical modifications and errors excepted.



Made in Germany