

DT-6016

Hydraulic System Cleaner

Hydraulic System Cleaner

Product Information

Produktinformation



Product Properties:

Removes operationally caused contamination and resins from the entire oil and lubrication system, the lubricating components of this highly effective formula protect the system, neutralise harmful acids and prevent the reforming of deposits and resins. The use of this product reduces wear and tear on the system resulting in longer service intervals, increased service life of the machine or equipment and "down-time" is kept to a minimum – all of which reduces the total costs.



Application Area

Suitable for all hydraulic systems.



Application

Add to the oil circulation system prior to the oil change.
Allow the engine to idle for approx. 15 minutes.
Afterwards carry out an oil change according to the manufacturer's instructions.



Consumption

150 ml for 1 Liter oil



Reaction time

approx. 15 min.



Technical data

Physical state: liquid
Color: yellow
Odor: aromatic
Boiling point: 180 - 220 ° C
Flash point: 63 ° C
Ignition temperature: > 200 ° C
Vapor pressure at 20 ° C: 20 hPa
insoluble in water



Available size

1L 5L 10L 25L 200L

1 Liter



Diatec International GmbH
Neuköllner Str 203 - 12357 Berlin
Email : info@dticc.com

Website : www.dticc.com
TEL: 0049177588641 / 00493098539728

DIATEC®

unsere technischen Informationen stützen sich auf sorgfältige Untersuchungen und wurden nach dem neuesten Stand zusammengestellt. Dennoch kann sie nur unverbindlich beraten, da Anwendung und Verarbeitungsmethoden nicht in unserem Einfluss liegen. Keine Haftung für Druckfehler. Technische Änderungen vorbehalten.

Our information is based on careful examination and may be considered as reliable. However, all information supplied is a non-binding advice. No liability for printing errors, technical modifications and errors excepted.



Made in Germany