

# DT-7036

## Adhesive Grease Spray (AGS)

Adhesive Grease Spray

### Product Information

Produktinformation



#### Product properties:

This product is a fully-synthetic, strongly adhesive lubricant for all joints, hinges, chains and many more. The product forms a long-lasting centrifugal and high-pressure resistant protection layer that repels water, is resistant to heat and salt, reliably protects against corrosion and considerably reduces wear and tear.



#### application Area

Perfectly suitable for lubrication of uncovered sections. For ropes, chains, cables, belts, gearboxes, cranes, construction machinery as well as for motorbikes and bicycles.



#### Application

Shake can well before use. Thoroughly clean the areastobe treated before application. Then spray the product evenly onto the areas to be lubricated.



#### Consumption

Depending on the application



#### Reaction time

Works permanently



#### Technical data

Physical state: aerosol  
Colour: brown  
Odour: characteristic  
Density at 68 °F: 0,86 - 0,87 g/cm<sup>3</sup>  
Water resistant



#### Available sizes

300 ml

1L 5L 10L 25L 200L



Diatec International GmbH  
Neuköllner Str 203 - 12357 Berlin

TEL: 0049177588641 / 00493098539728

Website : [www.dticc.com](http://www.dticc.com)  
Email : [info@dticc.com](mailto:info@dticc.com)

# DIATEC<sup>®</sup>

Our information is based on careful examination and may be considered as reliable. However, all information supplied is a non-binding advise. No liability for printing errors, technical modifications and errors excepted.



Made in Germany