

DT-7056

White Grease (PTFE)

White Grease

Product Information

Produktinformation



Product properties

Diatec White Grease guarantees an optimal long-term lubrication throughout the temperature range. The special formula contains Teflon which forms a centrifugal and high-pressure resistant protection layer that repels water, is resistant to heat and salt and reliably protects against corrosion.



application Area

In the industry and workshop area e.g. for corroded hinges, bolted connections, brake linkages and components, door latches, hinges, gears, springs, bearings, rubber components, 'o' rings, striker plates, window regulators, sliding shackles etc.



Application

Shake well before use. Thoroughly clean the areas to be treated before application. Spray evenly onto the parts to be lubricated from a distance of 20-30 cm. Move lubricated parts for several seconds to ensure total coverage.



Consumption

Depending on the application



Technical data

Physical state: aerosol
Colour: white
Odour: characteristic
Lower explosion limit: 0,6 Vol.-%
Ignition temperature: > 250 °C
Density at 68 °F: 0,70 g/cm³
Water resistant



Available sizes

1L 5L 10L 25L 200L

300 ml



Diatec International GmbH
Neuköllner Str 203 - 12357 Berlin Email : info@dticc.com
Website : www.dticc.com

TEL: 0049177588641 / 00493098539728

DIATEC

Our information is based on careful examination and may be considered as reliable. However, all information supplied is a non-binding advise. No liability for printing errors, technical modifications and errors excepted.



Made in Germany