

DT-7066

Power Lube Nano-Tec (PLNT)

Power Lube Nano-Tec

Product Information

Produktinformation



Product properties:

This multipurpose lubricant forms a highly efficient NANO anti-friction barrier between the moving parts. This barrier is created by the especially formulated NANO-clusters with their extreme wear and tear protection properties.

Benefits:

- forms an extremely resistant lubrication film
- ideal for use under high-pressure conditions
- water-repellent, displaces moisture, highly adhesive
- perfectly suitable for long-term application
- extended life-span of the treated parts
- highly effective protection against wear and tear
- excellent "run-dry" properties



application Area

Chains, ropes, rolls, bearings, chain inner bearings, gearwheels, worm gears, joints, clutches, wire ropes, hinges, o-rings, bowden cables, locks etc.



Application

Shake well before use! Thoroughly clean the parts to be treated. Afterwards evenly spray the product onto the areas to be treated and let it take effect for a while.



Consumption

Power Lube Nano-Tec
Depending on the application



Reaction time

Works permanently



Technical data

Physical state: aerosol
Colour: brown
Odour: mild
Density at 68 °F: 0.97 g/cm³
Water resistant



Available size

1L 5L 10L 25L 200L

300 ml



Diatec International GmbH
Neuköllner Str 203 - 12357 Berlin
Email : info@dticc.com
Website : www.dticc.com
TEL: 0049177588641 / 00493098539728

DIATEC[®]

Our information is based on careful examination and may be considered as reliable. However, all information supplied is a non-binding advise. No liability for printing errors, technical modifications and errors excepted.