

DT - 3046

Valves and Injection Cleaner

Product Information
Produktinformation



Product properties

High Performance Valves and Injection Cleaner. Power and Energy for all petrol engines.

- improves motor performance
- removes carbon deposits on valves, intake area and in the entire combustion chamber area
- removes deposits throughout the whole fuel injection system
- ensures a clean and powerful combustion
- optimizes emission values
- guarantees optimised injection dosage and fuel vapourisation
- gives optimal engine protection, increases the life span of the engine, ensures smooth and soft motor running



Application Area

For all petrol engines with carburettor, injection, direct injection (FSI, GDI, ...) and catalytic converters.



Application

Add every 6 months to the fuel system before filling up with petrol. Treats 80 litres of fuel.



Consumption

300 ml sufficient for up to 80 ltrs fuel. 1% of the tank volume for larger tanks.



Reaction time

Works during operation.



Technical data

Physical state: liquid
Colour: blue
Odour: aromatic
Initial boiling point and boiling range: 110 - 116 °C
Flashpoint: -5 °C
Lower explosion limit: 0,6 Vol.-%
Upper explosion limit: 12 Vol.-%
Ignition temperature: > 200 °C
Vapour pressure (at 68 °F): 20 hPa
Density at 68 °F: 0.78-0.82 g/cm³
Water resistant



Available size

1L 5L 10L 25L 200L



Diatec International GmbH
Neuköllner Str 203 - 12357 Berlin
Email : info@dticc.com
Website : www.dticc.com
TEL: 0049177588641 / 00493098539728

DIATEC®

Our information is based on careful examination and may be considered as reliable. However, all information supplied is a non-binding advise. No liability for printing errors, technical modifications and errors excepted.



Made in Germany