

DT-1056

Oil Anti Smoke (OAS)

Oil Anti Smoke



Product properties:

Innovative mixture of products which significantly reduces exhaust smoke and soot generation for all 4-stroke-, LPG and diesel powered engines. Ideal for vehicles with high consumption of oil. The product ensures optimal lubrication of all moving parts and reduces the oxidation of the engine oil. Due to this, the engine is noise will be lower, smoke is extremely reduced, the wear decreases and the lifetime of the unit is increased. The high viscosity prevents oil from entering the combustion chamber.



Area of application

For use in all 4-stroke, diesel and LPG powered engines. This product is compatible with all commercially available oils.



Application

Add to oil system. We recommend an oil system cleaning with Engine Cleaner before using this product. Total Oil volume according to manufacturer specifications must be observed.



Consumption

300ml sufficient for 5 liter of oil. Mixing ratio: 1:15



Reaction time

while engine is running



Technical data

Physical state: viscous
Colour: brown
Odour: mild
Flashpoint: > 100 °C
Density at 68 °F: 0.89 - 0.92 g/cm³
Water resistant



Available size

1L 5L 10L 25L 200L

Product Information

Produktinformation



Diatec International GmbH
Neuköllner Str 203 - 12357 Berlin Email : info@dticc.com
Website : www.dticc.com
TEL: 0049177588641 / 00493098539728

DIATEC®

Our information is based on careful examination and may be considered as reliable. However, all information supplied is a non-binding advise. No liability for printing errors, technical modifications and errors excepted.



Made in Germany