

Technical Data Sheet

Divinol B Classic

Product description

- semi-synthetic, non-water-miscible multi-purpose release agent
- solvent-free
- no discoloration of the concrete surface
- very economical in use
- free of waxes and silicones

Approval

Divinol B Classic is suitable for Minergie-Eco (Swiss label for ecological building).

Characteristics

Appearance:	clear
Colour / DIN ISO 2049:	lighter 4.0
Viscosity/0°C / ASTM D 7042 :	45 mm ² /s
Viscosity/20°C / ASTM D 7042 :	21 mm ² /s
Viscosity/40°C / ASTM D 7042 :	9.2 mm ² /s
Viscosity index / ASTM D 2270 :	94
Density/15°C / DIN EN ISO 12185:	860 kg/m ³
Pour point / DIN ISO 3016:	< -10 °C
Flash point (Cleveland) / DIN ISO 2592:	> 120 °C
Giscode:	BTM 10
Water hazardous class:	1

Application

Divinol B Classic can be used for all common types of formwork in concrete factories and in the building construction: for less or non-absorbent formwork (phenol resin formwork) as well as formwork made of plastic

08920

04/2017-08920-22

The statements made in this publication are according to our present knowledge. They do not absolve the user from own examinations. A legally binding assurance of certain properties or suitability for a specific use can not be derived from our statements. Possibly existing laws and regulations concerning the handling and use of our products have to be observed by the receiver of our products himself.

1 / 2

Technical Data Sheet

Divinol B Classic

material.

If used properly, **Divinol B Classic** does not allow direct contact of the formwork with the concrete surface. Thus, damages to the surface of the concrete can be prevented and re-working can be avoided. The life-time of the formwork will be extended and therefore the profitability in general. Moreover, an environmental hazard is excluded.

If used properly, **Divinol B Classic** does not influence negatively the subsequent treatment of the concrete surface (plastering, ceramics, wallpaper, paint).

Preparation of the emulsion

Divinol B Classic can be applied in the state at time of delivery by spraying, brushing or rolling without any problems.

Storage

Divinol B Classic is not sensitive to frost and can be used without any problems at all weather conditions. Any thickenings at temperatures below 0°C are reversible.

Miscellaneous

Reference object: DC Tower Wien.

08920

04/2017-08920-22

The statements made in this publication are according to our present knowledge. They do not absolve the user from own examinations. A legally binding assurance of certain properties or suitability for a specific use can not be derived from our statements. Possibly existing laws and regulations concerning the handling and use of our products have to be observed by the receiver of our products himself.

2 / 2