

# Technical Data Sheet

## Divinol Lithogrease G 421

---

### Product description

- high quality, semi-synthetic lithium complex soap grease
- work stable
- water resistant
- corrosion and oxidation resistant
- offers a very good wear protection
- shows goods pressure absorption capacity
- classification KP 2 P-30 as per DIN 51 825
- classification ISO-L-XCEHB 2 as per ISO/DIS 6743-9

### Approval

**Divinol Lithogrease G 421** complies to the requirement TL 9150-0075/2 of the German Army and is approved according to the NATO-Code G 421.

### Characteristics

Colour / Appearance:	yellow
Thickening agent:	Lithium complex soap
Operating temperature range:	-35°C - +160°C
NLGI-class / DIN 51 818:	2
Base oil viscosity/40°C / ASTM D 7042:	130 mm <sup>2</sup> /s
Water content / DIN 51 777/T1:	< 0,2 %
Dropping point / DIN ISO 2176:	> 220 °C
Worked penetration/0.1mm, 60 double strokes / DIN ISO 2137:	280
Worked penetration/0.1mm, 60 000 double strokes / DIN ISO 2137:	300
Water resistance / DIN 51807-1:	Evaluation level 1
Flow pressure at -30°C / DIN 51 805:	600 hPa
Oil separation / DIN 51 817:	ca. 2,5 %

20160

04/2017-20160-4

The statements made in this publication are according to our present knowledge. They do not absolve the user from own examinations. A legally binding assurance of certain properties or suitability for a specific use can not be derived from our statements. Possibly existing laws and regulations concerning the handling and use of our products have to be observed by the receiver of our products himself.

1 / 2

# Technical Data Sheet

## Divinol Lithogrease G 421

---

Corrosion protection behaviour (EMCOR-test) / DIN 51 802:	0/0
Oxidation resistance 100°C/100h / DIN 51 808:	0.2 bar
VKA welding load / DIN 51 350/T4:	4000 N

## Application

**Divinol Lithogrease G 421** is especially used for the lubrication of mechanically and thermally extreme-loaded roller and slide bearings, e. g. wheel hubs and release bearings of couplings. Due to its content of synthesis oil **Divinol Lithogrease G 421** offers longer service lives compared to mineral oil based greases. Thus, the additional lubrication intervals can be prolonged which in consequence reduces the consumption of grease.

20160

04/2017-20160-4

The statements made in this publication are according to our present knowledge. They do not absolve the user from own examinations. A legally binding assurance of certain properties or suitability for a specific use can not be derived from our statements. Possibly existing laws and regulations concerning the handling and use of our products have to be observed by the receiver of our products himself.

2 / 2