

# Technical Data Sheet

## Divinol HLP ISO 10

---

### Product description

- high pressure hydraulic oil
- on the basis of mineral oil
- with anti-oxidation and anti-corrosion agents
- with wear and friction reducing additives
- fulfils the requirements to hydraulic oils according to DIN 51 524 part 2, HLP

### Specification

**International Specifications:** SEB 181 222, AFNOR NF-E 48603, ASLE 70-1, 70-2 and 70-3, David Brown S1.53.101, VDMA 24318, U. S. Steel 126/127, CETOP RP91H, Vickers I-286-S3, Denison Hydraulics HF-2, Vickers M-2950-S.

### Characteristics

Colour / DIN ISO 2049:	lighter 1.5
Density/15°C / DIN EN ISO 12185:	860 kg/m <sup>3</sup>
Viscosity/40°C / ASTM D 7042 :	10 mm <sup>2</sup> /s
Viscosity index / ASTM D 2270 :	90
Flash point (Cleveland) / DIN ISO 2592:	> 160 °C
Pour point / DIN ISO 3016:	< -30 °C
Corrosion protection towards steel / DIN ISO 7120:	Corrosion degree: pass
Corrosion effect on copper 3h/100°C / DIN EN ISO 2160:	Corrosion degree 1b
Loading capacity according to Brugger / DIN 51 347:	27 N/mm <sup>2</sup>
Air release characteristics at 50°C / DIN ISO 9120:	2 min

20530

04/2017-20530-8

The statements made in this publication are according to our present knowledge. They do not absolve the user from own examinations. A legally binding assurance of certain properties or suitability for a specific use can not be derived from our statements. Possibly existing laws and regulations concerning the handling and use of our products have to be observed by the receiver of our products himself.

1 / 2

# Technical Data Sheet

## Divinol HLP ISO 10

---

### Application

Divinol HLP ISO 10 is used for all kinds of hydraulic aggregates, for which the use of HLP-alloyed oils is prescribed.

20530

04/2017-20530-8

The statements made in this publication are according to our present knowledge. They do not absolve the user from own examinations. A legally binding assurance of certain properties or suitability for a specific use can not be derived from our statements. Possibly existing laws and regulations concerning the handling and use of our products have to be observed by the receiver of our products himself.

2 / 2