

# Technical Data Sheet

## Divinol Bio\*-Kettenöl 220

---

### Product description

Divinol Bio\*-Kettenöl 220 is a eco-friendly product specially designed and tested for high performance saws and harvesters. Environmentally friendly as based on renewable resources and readily biodegradable. Divinol Bio\*-Kettenöl 220 can be used all year round and has excellent adhesion, anti-wear and corrosion protection properties. The product offers a long term gumming protection to prevent sticking of the chain. Divinol Bio\*-Kettenöl 220 can be used in high-performance saws or harvesters, where particularly high viscosity oils are needed.

\* = The word "bio" refers to biodegradability according to OECD 301 F.  
The limit according to OECD 301 F was achieved within 28 days.

### Characteristics

Colour / DIN ISO 2049:	brighter 2,0
Viscosity/40°C / ASTM D 7042 :	240 mm <sup>2</sup> /s
Density/15°C / DIN EN ISO 12185:	925 kg/m <sup>3</sup>
Pour point / DIN ISO 3016:	-29 °C
Loading capacity according to Brugger / DIN 51 347:	37 N/mm <sup>2</sup>
VKA welding load / DIN 51 350/T4:	2200 N
Flash point (Cleveland) / DIN ISO 2592:	> 250 °C

### Application

Divinol Bio\*-Kettenöl 220 offers due to its definitive adhesive strength and the use of wear preventive additives best lubrication of high performance chain saws in e.g. wood working machines. Best lubrication even under hard conditions of use due to the high performance reserves. The product is stable for at least 18 months. For cleaning Divinol recommends our DIVINOL Gerätereiniger Forte.

26110

04/2017-26110-11

The statements made in this publication are according to our present knowledge. They do not absolve the user from own examinations. A legally binding assurance of certain properties or suitability for a specific use can not be derived from our statements. Possibly existing laws and regulations concerning the handling and use of our products have to be observed by the receiver of our products himself.

1 / 1