

Technical Data Sheet

Divinol Kettenöl TS 220

Product description

Partly synthetic high-performance saw-chain oil. Compared with traditional biological chain oils based on rape oil, this new development has the advantage that there is no gumming any more. Additionally, a significantly higher minimum durability of 7 years can be guaranteed. Divinol Kettenöl TS 220 can be used in high power saws or harvesters.

Divinol Kettenöl TS 220 offers following advantages:

- Up to 100% resin-free
- Best wear protection
- Optimum adhesion properties
- Economic consumption
- Clear colour, no unattractive stains in visible sections
- Pleasant odour
- Minimum durability 7 years (by correct storage!)
- suitable for harvesters

Characteristics

Colour / DIN ISO 2049:	< 3,5
Viscosity/40°C / ASTM D 7042 :	220 mm ² /s
Density/15°C / DIN EN ISO 12185:	905 kg/m ³
Pour point / DIN ISO 3016:	< -20 °C
Loading capacity according to Brugger / DIN 51 347:	34 N/mm ²

Application

This newly developed chain-saw oil is ideal for lubricating high performance chain saws of all types. An optimum full greasing is guaranteed in summer and winter even under difficult usage conditions, due to high performance reserves. For cleaning chain saws etc.. Divinol recommends DIVINOL Gerätereiniger Forte.

27770

04/2017-27770-6

The statements made in this publication are according to our present knowledge. They do not absolve the user from own examinations. A legally binding assurance of certain properties or suitability for a specific use can not be derived from our statements. Possibly existing laws and regulations concerning the handling and use of our products have to be observed by the receiver of our products himself.

1 / 1