

# Technical Data Sheet

## Divinol Zentralhydraulikfluid S

---

### Product description

Divinol Zentralhydraulikfluid S is a fully synthetic oil that meets the highest requirements. This product offers a high thermal stability, optimum foaming properties and good aging resistance. In addition, the product has an excellent low-temperature behavior. Due to the special additives Divinol Zentralhydraulikfluid S offers a high amount of corrosion protection component as well as maximum wear protection.

### Manufacturer performance

VW TL 521 46 (G00200 / G00400)  
Audi P/N G002000 / VW TL 52146  
Audi P/N G002012  
Chrysler MS-1872  
Chrysler MS-5931, P/N 04883077  
Chrysler MS-9602, ATF+4  
Chrysler MS-10838, P/N 05142893AA  
Ford M2C195-A  
Ford M2C204-A (extended temp range)  
GM P/N 89021184  
GM 9985010, P/N 1052884  
GM 9985835, P/N 12345866 (cold climate)  
Hyundai / Kia PSF-3  
Hyundai / Kia PSF-4  
Mercedes Benz 236.3, P/N 000 989 88 03  
Mercedes Benz 345.0, P/N 001 989 24 03  
MAN M 3289  
Mitsubishi PS Fluid  
Mitsubishi Diamond SP III  
Nissan PSF-II  
Pentosin CHF 7.1  
Pentosin CHF 11S  
Pentosin CHF 202  
Saab P/N (45) 30 09 800  
Saab P/N 30 32 380  
Subaru P/N K0209A0080  
Toyota PSF Type EH, P/N 008886-01  
VW P/N G002000  
VW P/N G002012  
PSA S 712710  
Volvo P/N 1161529

28360

04/2017-28360-8

The statements made in this publication are according to our present knowledge. They do not absolve the user from own examinations. A legally binding assurance of certain properties or suitability for a specific use can not be derived from our statements. Possibly existing laws and regulations concerning the handling and use of our products have to be observed by the receiver of our products himself.

1 / 2

# Technical Data Sheet

## Divinol Zentralhydraulikfluid S

---

### Characteristics

Appearance:	green
Viscosity/40°C / ASTM D 7042 :	27 mm <sup>2</sup> /s
Viscosity/100°C / ASTM D 7042 :	6.5 mm <sup>2</sup> /s
Viscosity index / ASTM D 2270 :	≥190
Density/15°C / DIN EN ISO 12185:	830 kg/m <sup>3</sup>
Pour point / DIN ISO 3016:	≤ -39°C
Flash point (Cleveland) / DIN ISO 2592:	≥ 210 °C

### Application

Suitable for central hydraulic systems (convertible top, steering, stability and traction systems), hydrostatic drives, level control, hydropneumatic suspension as well as power steering and damping. Divinol Zentralhydraulikfluid S is also suitable for refilling. Please see manufacturer's instructions.

28360

04/2017-28360-8

The statements made in this publication are according to our present knowledge. They do not absolve the user from own examinations. A legally binding assurance of certain properties or suitability for a specific use can not be derived from our statements. Possibly existing laws and regulations concerning the handling and use of our products have to be observed by the receiver of our products himself.

2 / 2