

# Technical Data Sheet

## Divinol Profi Lube KWS

---

### Product description

Anti-corrosion spray especially suitable for preservation of commercial vehicles, all kinds of machines, spare parts, tools and further high-quality device. The product has a bright film, nearly transparent and becomes solid as well as touch-dry without being brittle. Additionally the product is also suitable for framing elements in order to avoid contact corrosion. With an adequate packaging the product is also suitable for maritime climate.

Special use for communities to conserve snow ploughs and gritters during and after winter service.

### Characteristics

|   |                       |
|---|-----------------------|
| Appearance:                                     | beige, thixotrop      |
| Type of protective film:                        | dry, touchable        |
| Density/15°C / DIN EN ISO 12185:                | 830 kg/m <sup>3</sup> |
| Colour of the protective film:                  | beige                 |
| Flash point (Pensky-Martens) / DIN EN ISO 2719: | > 38 °C               |
| Kesternich test / DIN EN ISO 6270-2:            | 40 turns              |
| Salt spray test / DIN EN ISO 9227:              | 100 hour(s)           |

### Application

**Divinol Profi Lube KWS** is applied by spraying. Amount used per square meter approx. 30-50 grams. The protective film should be applied several times. Treated surfaces can be cleaned with Divinol Gerätereiniger Forte.

Do not spray on hot surfaces!

### Degreasing

Divinol Gerätereiniger Forte

33210 LK

04/2017-33210 LK-6

The statements made in this publication are according to our present knowledge. They do not absolve the user from own examinations. A legally binding assurance of certain properties or suitability for a specific use can not be derived from our statements. Possibly existing laws and regulations concerning the handling and use of our products have to be observed by the receiver of our products himself.

1 / 1