

Technical Data Sheet

Divinol Spezial 2000 HD 10W

Product description

Divinol Spezial 2000 HD 10W has high power reserves against wear and cold sludge formation. It provides optimum lubrication, even under difficult conditions. An oil with a particularly high resistance to aging.

Specification

API SJ/CF

Manufacturer performance

MB-Approval 227.0/228.0; MAN 270; Volvo VDS

Divinol Recommendation: ACEA E1/E2

Characteristics

SAE Grade:	10W
Colour / DIN ISO 2049:	3,5
Viscosity/40°C / ASTM D 7042 :	28.6 mm ² /s
Viscosity/100°C / ASTM D 7042 :	4.1 mm ² /s
Viscosity index / ASTM D 2270 :	123
Density/15°C / DIN EN ISO 12185:	0,870 g/cm ³
Pour point / DIN ISO 3016:	<-25°C
Flash point (Cleveland) / DIN ISO 2592:	>200 °C
TBN:	10.5 mgKOH/g

Application

All purpose HD single grade engine oil for Otto and Diesel engines and stationary motors. The mix of proven base oils with additives ensures effective wear and corrosion protection. Also suitable as hydraulic medium for machines
48450 04/2017-48450-8

The statements made in this publication are according to our present knowledge. They do not absolve the user from own examinations. A legally binding assurance of certain properties or suitability for a specific use can not be derived from our statements. Possibly existing laws and regulations concerning the handling and use of our products have to be observed by the receiver of our products himself.

1 / 2

Technical Data Sheet

Divinol Spezial 2000 HD 10W

and vehicles when matching OEM's specifications.

48450

04/2017-48450-8

The statements made in this publication are according to our present knowledge. They do not absolve the user from own examinations. A legally binding assurance of certain properties or suitability for a specific use can not be derived from our statements. Possibly existing laws and regulations concerning the handling and use of our products have to be observed by the receiver of our products himself.

2 / 2