

# Technical Data Sheet

## Divinol Spezial 2000 HD 30

---

### Product description

Divinol Spezial 2000 HD 30 has high reserve capacities against wear and sludge. The product offers optimal lubrication, even under difficult conditions as well as a very high oxidation stability.

### Specification

API SJ/CF

### Manufacturer performance

MB-Approval 227.0/228.0; MAN 270; Volvo VDS

Divinol Recommendation: ACEA E1/E2

### Characteristics

SAE Grade:	30
Viscosity/40°C / ASTM D 7042 :	75
Viscosity/100°C / ASTM D 7042 :	10.9 mm <sup>2</sup> /s
Viscosity index / ASTM D 2270 :	113
Density/15°C / DIN EN ISO 12185:	880 kg/m <sup>3</sup>
Pour point / DIN ISO 3016:	-31 °C
Flash point (Cleveland) / DIN ISO 2592:	> 210 °C

### Application

All purpose HD single grade engine oil for Otto and Diesel engines and stationary motors. The mix of proven base oils with additives ensures effective wear and corrosion protection. Also suitable as hydraulic medium for machines and vehicles when matching OEM's specifications.

48470

04/2017-48470-11

The statements made in this publication are according to our present knowledge. They do not absolve the user from own examinations. A legally binding assurance of certain properties or suitability for a specific use can not be derived from our statements. Possibly existing laws and regulations concerning the handling and use of our products have to be observed by the receiver of our products himself.

1 / 2

# Technical Data Sheet

## Divinol Spezial 2000 HD 30

---

48470

04/2017-48470-11

The statements made in this publication are according to our present knowledge. They do not absolve the user from own examinations. A legally binding assurance of certain properties or suitability for a specific use can not be derived from our statements. Possibly existing laws and regulations concerning the handling and use of our products have to be observed by the receiver of our products himself.

2 / 2