

Technical Data Sheet

Divinol HLP ISO 22

Product description

- high pressure hydraulic oil
- on the basis of mineral oil
- with anti-oxidation and anti-corrosion agents
- with wear and friction reducing additives
- fulfils the requirements to hydraulic oils according to DIN 51 524 part 2, HLP

Specification

International Specifications: SEB 181 222, AFNOR NF-E 48603, ASLE 70-1, 70-2 and 70-3, David Brown S1.53.101, VDMA 24318, U. S. Steel 126/127, CETOP RP91H, Vickers I-286-S3, Denison Hydraulics HF-2, Vickers M-2950-S.

Characteristics

Colour / DIN ISO 2049:	max. 2.0
Density/15°C / DIN EN ISO 12185:	860 kg/m ³
Viscosity/40°C / ASTM D 7042 :	22 mm ² /s
Viscosity index / ASTM D 2270 :	100
Flash point (Cleveland) / DIN ISO 2592:	> 190 °C
Pour point / DIN ISO 3016:	≤ -21 °C

Application

Divinol HLP ISO 22 is used for all kinds of hydraulic aggregates, for which the use of HLP-alloyed oils is prescribed.

48850

04/2017-48850-7

The statements made in this publication are according to our present knowledge. They do not absolve the user from own examinations. A legally binding assurance of certain properties or suitability for a specific use can not be derived from our statements. Possibly existing laws and regulations concerning the handling and use of our products have to be observed by the receiver of our products himself.

1 / 1