

# Technical Data Sheet

## Divinol Multilight FO 2 5W-30

---

### Product description

Divinol Multilight FO 2 5W-30 is a special semi-synthetic oil for modern Ford diesel and otto motors. Especially during start and warm-up phase this quality motor oils guarantees fast oiling of the motor. The new Ford specification WSS M2C 913D assures fuel saving properties.

### Specification

ACEA A5/B5

### Manufacturer approval

Ford WSS-M2C-913 D

### Manufacturer performance

Ford WSS-M2C-913-A; Ford WSS-M2C-913-B; Ford WSS-M2C-913-C; Ford WSS-M2C-925-A; PSA B71 2296; Renault RN 0700; Iveco 18-1811

### Characteristics

SAE Grade:	5W-30
Appearance:	L 3,0
Viscosity/40°C / ASTM D 7042 :	58 mm <sup>2</sup> /s
Viscosity/100°C / ASTM D 7042 :	10.2 mm <sup>2</sup> /s
Viscosity index / ASTM D 2270 :	167
Density/15°C / DIN EN ISO 12185:	0,85 g/cm <sup>3</sup>
Pour point / DIN ISO 3016:	-45°C
Flash point (Cleveland) / DIN ISO 2592:	235°C
TBN:	8.5 mgKOH/g

49170

05/2017-49170-13

The statements made in this publication are according to our present knowledge. They do not absolve the user from own examinations. A legally binding assurance of certain properties or suitability for a specific use can not be derived from our statements. Possibly existing laws and regulations concerning the handling and use of our products have to be observed by the receiver of our products himself.

1 / 2

# Technical Data Sheet

## Divinol Multilight FO 2 5W-30

---

### Application

Divinol Multilight FO 2 5W-30 is suitable for otto and diesel motors according to OEMs regulations. In particular suitable for Ford vehicles.

49170

05/2017-49170-13

The statements made in this publication are according to our present knowledge. They do not absolve the user from own examinations. A legally binding assurance of certain properties or suitability for a specific use can not be derived from our statements. Possibly existing laws and regulations concerning the handling and use of our products have to be observed by the receiver of our products himself.

2 / 2