

Technical Data Sheet

Divinol Multilight FO 5W-30

Product description

Divinol Multilight FO 5W-30 is a modern multi-grade light-running engine oil of the newest generation in synthetic technology. The conventional and unconventional basic oils equipped with a modern additive recipe guarantee an optimum viscosity-temperature behaviour. It prevents effectively deposits, reduces friction losses, saves fuel and guarantees a longer engine life.

Specification

API SL/CF; ACEA A5/B5

Manufacturer performance

Ford WSS-M2C-912 A; Ford WSS-M2C-913 A/B

Characteristics

SAE Grade:	5W30
Appearance:	L4.5
Viscosity/40°C / ASTM D 7042 :	64 mm ² /s
Viscosity/100°C / ASTM D 7042 :	11 mm ² /s
Viscosity index / ASTM D 2270 :	168
Density/15°C / DIN EN ISO 12185:	0.85 g/cm ³
Pour point / DIN ISO 3016:	-42°C
Flash point (Cleveland) / DIN ISO 2592:	233 °C
TBN:	8 mgKOH/g

49200

05/2017-49200-10

The statements made in this publication are according to our present knowledge. They do not absolve the user from own examinations. A legally binding assurance of certain properties or suitability for a specific use can not be derived from our statements. Possibly existing laws and regulations concerning the handling and use of our products have to be observed by the receiver of our products himself.

1 / 2

Technical Data Sheet

Divinol Multilight FO 5W-30

Application

Divinol Multilight FO 5W-30 is recommended for Otto- and Dieselmotors including turbo-superchargers and catalysers considering the manufacturers instructions in each case.

49200

05/2017-49200-10

The statements made in this publication are according to our present knowledge. They do not absolve the user from own examinations. A legally binding assurance of certain properties or suitability for a specific use can not be derived from our statements. Possibly existing laws and regulations concerning the handling and use of our products have to be observed by the receiver of our products himself.

2 / 2