

Technical Data Sheet

Divinol Syntholight MBX 5W-30

Product description

Divinol Syntholight MBX 5W-30 is A modern smooth-running high-performance engine oil among the best of its class, which can be used for the extended maintenance intervals in vehicles of new car generations. This high-performance engine oil is formulated for use in modern Mercedes petrol engines, but also suitable for diesel engines. It enables an efficient supply of advanced car engines while keeping maintenance efforts as low as possible.

Specification

API SL; ACEA A3/B4

Manufacturer approval

MB-Approval 229.5

Manufacturer performance

VW 502.00/505.00; Renault RN 0700; BMW LL-01

Characteristics

Viscosity/40°C / ASTM D 7042 :	75 mm ² /s
Viscosity/100°C / ASTM D 7042 :	13 mm ² /s
Viscosity index / ASTM D 2270 :	170
Density/15°C / DIN EN ISO 12185:	860 kg/m ³
Pour point / DIN ISO 3016:	<-35 °C
Flash point (Cleveland) / DIN ISO 2592:	>200°C
TBN:	12 mgKOH/g

49210

05/2017-49210-13

The statements made in this publication are according to our present knowledge. They do not absolve the user from own examinations. A legally binding assurance of certain properties or suitability for a specific use can not be derived from our statements. Possibly existing laws and regulations concerning the handling and use of our products have to be observed by the receiver of our products himself.

1 / 2

Technical Data Sheet

Divinol Syntholight MBX 5W-30

Application

This synthetic high-performance engine oil is ideal for an application in all spark-ignition and diesel engines according to the most advanced technologies. High lubricating safety and substantially longer maintenance intervals are the benefit.

49210

05/2017-49210-13

The statements made in this publication are according to our present knowledge. They do not absolve the user from own examinations. A legally binding assurance of certain properties or suitability for a specific use can not be derived from our statements. Possibly existing laws and regulations concerning the handling and use of our products have to be observed by the receiver of our products himself.

2 / 2