

Technical Data Sheet

Divinol Syntholight SL GM 5W-30

Product description

##ARTBEZ1## is a smooth-running engine oil made according to the most modern synthesis technology. ##ARTBEZ1## ensures on the one hand a quick oiling of the engine even at low temperatures and on the other hand a sufficiently thick lubricating film at high oil temperatures. An excellent oxidation stability and well-balanced additives with high active substance reserves provide protection against oil sludge, coking, and corrosion.

Specification

API SL; ACEA A3/B4

Manufacturer performance

Opel GM-LL-A-025; Opel GM-LL-B-025

Characteristics

Viscosity/40°C / ASTM D 7042 :	61 mm ² /s
Viscosity/100°C / ASTM D 7042 :	10.3 mm ² /s
Viscosity index / ASTM D 2270 :	186
Density/15°C / DIN EN ISO 12185:	860 kg/m ³
Pour point / DIN ISO 3016:	<-35 °C
Flash point (Cleveland) / DIN ISO 2592:	230 °C

Application

##ARTBEZ1## is a high-performance smooth-running engine oil designed for Otto and diesel engines. It is especially recommended for use in Opel engines.

49240

05/2017-49240-7

The statements made in this publication are according to our present knowledge. They do not absolve the user from own examinations. A legally binding assurance of certain properties or suitability for a specific use can not be derived from our statements. Possibly existing laws and regulations concerning the handling and use of our products have to be observed by the receiver of our products himself.

1 / 1