Technical Data Sheet

Divinol Syntholight 03 5W-30

Product description

High-performance engine oil on the basis of the most advanced technology.known as third longlife generation for almost all private cars of VW group. This Longlife engine oil guarantees longest oil-change. The product provides an optimum lubrication safety during the whole maintenance interval period. The low HTHS viscosity allows maximum fuel savings and therefore contributes to relieve stress on the environment.

Specification

ACEA C2-12/C3-12

Divinol Recommendation:

VW 504.00/507.00; MB-Approval 229.51; BMW Longlife-04; Porsche C30

Characteristics

SAE Grade:	5W-30
Viscosity/40°C / ASTM D 7042 :	73 mm²/s
Viscosity/100°C / ASTM D 7042 :	10.9 mm²/s
Viscosity index / ASTM D 2270 :	>=160
Density/15°C / DIN EN ISO 12185:	0,85 g/m³
Pour point / DIN ISO 3016:	<= -27°C
Flash point (Cleveland) / DIN ISO 2592:	>210°C
TBN:	6 mgKOH/g

Application

Divinol Syntholight 03 5W-30 is ideal for product reduction. Except for VW R5 and V10 engines produced before 2007.

49251

04/2017-49251-13

The statements made in this publication are according to our present knowledge. They do not absolve the user from own examinations. A legally binding assurance of certain properties or suitability for a specific use can not be derived from our statements. Possibly existing laws and regulations concerning the handling and use of our products have to be observed by the receiver of our products himself.

1/2



ZG Division: Divinol Lubricants & Release Agents Zeller+Gmelin GmbH & Co. KG Schlossstr. 20 - 73054 Eislingen/Fils Tel. +49 7161 802-0 - Fax +49 7161 802-230 www.zeller-gmelin.de - dst@zeller-gmelin.de



Technical Data Sheet

Divinol Syntholight 03 5W-30

49251

04/2017-49251-13

The statements made in this publication are according to our present knowledge. They do not absolve the user from own examinations. A legally binding assurance of certain properties or suitability for a specific use can not be derived from our statements. Possibly existing laws and regulations concerning the handling and use of our products have to be observed by the receiver of our products himself.

2/2



ZG Division: Divinol Lubricants & Release Agents Zeller+Gmelin GmbH & Co. KG Schlossstr. 20 - 73054 Eislingen/Fils Tel. +49 7161 802-0 - Fax +49 7161 802-230 www.zeller-gmelin.de - dst@zeller-gmelin.de

