

Technical Data Sheet

Divinol Multimax LoSAPS 5W-30

Product description

Divinol Multimax LoSAPS 5W-30 is a MHPD (Maximum High Performance Diesel) oil with high quality protective properties for latest truck diesel engines. The oil was developed specifically for low-emission LOW SAPS EURO V and EURO VI engines. Thus, this motor oil is for NOx and particulate reduction systems in combination with low sulfur containing diesel (max. 50 ppm). Additionally, this product offers significant fuel savings and favorable economic conditions.

Advantages:

- very good protection against piston deposits
- effective oxidation resistance
- offers significant fuel savings and favorable economic conditions
- low oil consumption due to lower evaporation loss
- longer oil drain intervals (depending on the manufacturer's instructions)

Specification

API CI-4; ACEA E6-12/ E7-12

Manufacturer approval

MB-Approval 228.51; MAN M 3477; Volvo VDS III; Renault RLD-2; Mack EO-N

Manufacturer performance

Volvo CNG; MAN 3271-1; MTU Type 3.1; Deutz DQC IV-05 / IV-10 LA; Caterpillar ECF-2; DAF; IVECO 18-1804 CLASSE TLS E6

Characteristics

SAE Grade:	5W-30
Viscosity/40°C / DIN 51 562:	65 mm ² /s

49270

10/2015-49270-14

The statements made in this publication are according to our present knowledge. They do not absolve the user from own examinations. A legally binding assurance of certain properties or suitability for a specific use can not be derived from our statements. Possibly existing laws and regulations concerning the handling and use of our products have to be observed by the receiver of our products himself.

1 / 2

Technical Data Sheet

Divinol Multimax LoSAPS 5W-30

Viscosity/100°C / DIN 51 562:	11 mm ² /s
Viscosity index / DIN ISO 2909:	> 160
Density/15°C / DIN 51 757:	854 kg/m ³
Pour point / DIN ISO 3016:	< -40°C
Flash point (Cleveland) / DIN ISO 2592:	> 215°C

Application

Divinol Multimax LoSAPS 5W-30 is recommended for heavy-duty diesel truck engines, including turbochargers and catalyts for longest oil drain intervals. Stick to manufacturer's instructions.

49270

10/2015-49270-14

The statements made in this publication are according to our present knowledge. They do not absolve the user from own examinations. A legally binding assurance of certain properties or suitability for a specific use can not be derived from our statements. Possibly existing laws and regulations concerning the handling and use of our products have to be observed by the receiver of our products himself.

2 / 2