

Technical Data Sheet

Divinol Syntholight R 5W-30

Product description

Divinol Syntholight R 5W-30 is a special synthesis oil for modern petrol and diesel engines with low ash content. This quality motor oil provides fast lubrication, especially in start and warm-up phase. Various Renault models need this special motor oil which is tuned to the latest generation of diesel particulate filters.

Specification

ACEA C1/C4

Manufacturer approval

Renault RN 0720

Manufacturer performance

MB-Approval 226.51; Ford WSS-M2C934-B

Characteristics

SAE Grade:	5W30
Ash / Sulfate DIN 51575:	0.5 %
Colour / DIN ISO 2049:	< 4,0
Viscosity/40°C / ASTM D 7042 :	65 mm ² /s
Viscosity/100°C / ASTM D 7042 :	10.9 mm ² /s
Viscosity index / ASTM D 2270 :	>170
Density/15°C / DIN EN ISO 12185:	855 kg/m ³
Pour point / DIN ISO 3016:	<-35°C
Flash point (Cleveland) / DIN ISO 2592:	>210°C

49350

05/2017-49350-15

The statements made in this publication are according to our present knowledge. They do not absolve the user from own examinations. A legally binding assurance of certain properties or suitability for a specific use can not be derived from our statements. Possibly existing laws and regulations concerning the handling and use of our products have to be observed by the receiver of our products himself.

1 / 2

Technical Data Sheet

Divinol Syntholight R 5W-30

Application

Divinol Syntholight R 5W-30 is recommended for gasoline and diesel engines (also LPG/CNG) in compliance with manufacturer's instructions, especially for french cars with exhaust aftertreatment system.

49350

05/2017-49350-15

The statements made in this publication are according to our present knowledge. They do not absolve the user from own examinations. A legally binding assurance of certain properties or suitability for a specific use can not be derived from our statements. Possibly existing laws and regulations concerning the handling and use of our products have to be observed by the receiver of our products himself.

2 / 2