

# Technical Data Sheet

## Divinol Multimax Advanced 5W30

---

### Product description

Divinol Multimax Advanced 5W30 is a MHPD (Maximum High Performance Diesel) oil with high quality protective properties for latest truck diesel engines. The oil was developed specifically for low-emission LOW SAPS EURO V and EURO VI engines. Thus, this motor oil is for NOx and diesel particulate filter in combination with low sulfur containing diesel (max. 50 ppm). In particular, commercial vehicles with EGR, SCR and diesel particulate filters require an oil quality according Divinol Multimax Advanced 5W30. In addition, Divinol Multimax Advanced 5W30 easily be used in older vehicles and offers the possibility of oil stock reduction.

### Advantages:

- very good protection against piston deposits
- effective oxidation resistance
- offers significant fuel savings and favorable economic conditions
- low oil consumption due to lower evaporation loss
- longer oil drain intervals (depending on the manufacturer's instructions)

### Specification

ACEA E6-12/E7-12/E9-12; API CJ-4/SN; JASO DH-2

### Manufacturer approval

MB-Approval 228.51;MB-Approval 228.31; MAN 3677; MAN 3477; MAN 3271-1; Volvo VDS 4; Renault RLD 3; Mack EO-O PP

### Manufacturer performance

Volvo CNG; Mack EO-N PP; Caterpillar ECF-3; Deutz DQC IV-10 LA

Trucks: Divinol Multimax Advanced 5W30 also provides the solution for SCANIA LDF-3 to optimize engine oil specification range.

### Characteristics

49360

11/2014-49360-12

The statements made in this publication are according to our present knowledge. They do not absolve the user from own examinations. A legally binding assurance of certain properties or suitability for a specific use can not be derived from our statements. Possibly existing laws and regulations concerning the handling and use of our products have to be observed by the receiver of our products himself.

1 / 2

# Technical Data Sheet

## Divinol Multimax Advanced 5W30

---

SAE Grade:	5W30
Ash / Sulfate DIN 51575:	0.9 %
Colour / DIN ISO 2049:	4
Viscosity/40°C / DIN 51 562:	65 mm <sup>2</sup> /s
Viscosity/100°C / DIN 51 562:	11.3 mm <sup>2</sup> /s
Viscosity index / DIN ISO 2909:	170
Density/15°C / DIN 51 757:	0,856 g/cm <sup>3</sup>
Pour point / DIN ISO 3016:	-35 °C
Flash point (Cleveland) / DIN ISO 2592:	216 °C
TBN:	9.6 mgKOH/g

## Application

Divinol Multimax Advanced 5W30 is recommended for heavy-duty diesel truck engines, including turbochargers and catalysts for longest oil drain intervals. Stick to manufacturer's instructions.

49360

11/2014-49360-12

The statements made in this publication are according to our present knowledge. They do not absolve the user from own examinations. A legally binding assurance of certain properties or suitability for a specific use can not be derived from our statements. Possibly existing laws and regulations concerning the handling and use of our products have to be observed by the receiver of our products himself.

2 / 2