

Technical Data Sheet

Divinol Spezial 2000 HD 20

Product description

Divinol Spezial 2000 HD 20 shows high reserve capacities against wear and formation of lime foam. It offers optimum lubrication, even under difficult circumstances. Also suitable for retarder and hydraulic systems. An oil with very high oxidation stability.

Specification

API SG/CF-4/CF-2

Manufacturer performance

MB-Approval 227.0/228.0; MAN 270; MTU Type 1

Divinol Recommendation: ACEA E1/E2

Characteristics

SAE Grade:	20
Viscosity/40°C / ASTM D 7042 :	42 mm ² /s
Viscosity/100°C / ASTM D 7042 :	7.5 mm ² /s
Viscosity index / ASTM D 2270 :	142
Density/15°C / DIN EN ISO 12185:	870 kg/m ³
Pour point / DIN ISO 3016:	<-20°C
Flash point (Cleveland) / DIN ISO 2592:	>220 °C

Application

All purpose HD single grade engine oil for Otto and Diesel engines with and without supercharging. The alloy of proven base oils with modern additives ensures effective wear and corrosion protection. Also suitable as hydraulic medium for vehicles when matching OEM's specifications.

49421

04/2017-49421-4

The statements made in this publication are according to our present knowledge. They do not absolve the user from own examinations. A legally binding assurance of certain properties or suitability for a specific use can not be derived from our statements. Possibly existing laws and regulations concerning the handling and use of our products have to be observed by the receiver of our products himself.

1 / 2

Technical Data Sheet

Divinol Spezial 2000 HD 20

49421

04/2017-49421-4

The statements made in this publication are according to our present knowledge. They do not absolve the user from own examinations. A legally binding assurance of certain properties or suitability for a specific use can not be derived from our statements. Possibly existing laws and regulations concerning the handling and use of our products have to be observed by the receiver of our products himself.

2 / 2