Technical Data Sheet

Divinol Syntholight Top 5W40

Product description

Divinol Syntholight Top 5W40 is a smooth running engine oil based on the most modern HC synthesis technology. This product guarantees excellent running properties, low abrasion and fuel savings due to the reduction of friction as well as a fine cold starting performance. The combination of HC synthetic base oils with a high-grade additive package ensures an outstanding engine oil. Divinol Syntholight Top 5W40 has a high resistance against oxidation and the well balanced additive system avoids oil sludge in the motor.

Advantages:

- · unique dispersing properties ensure excellent engine cleanliness
- · outstanding cleaning properties of all engine components
- · corrosion treatment
- · excellent anti-wear and
- · outstanding lubricant reliability

Specification

ACEA A3-12/B4-12; API SN/CF; JASO MA-2

Manufacturer approval

MB-Approval 229.5

Manufacturer performance

BMW Longlife-01; MB-Approval 226.5; GM-LL-A-025; GM-LL-B-025; Porsche A40; VW 505.00/502.00; Renault RN 0700/0710

Characteristics

 SAE Grade:
 5W40

 Ash / Sulfate DIN 51575:
 1.2 %

 Colour / DIN ISO 2049:
 L 4,5

49430 04/2017-49430-10

The statements made in this publication are according to our present knowledge. They do not absolve the user from own examinations. A legally binding assurance of certain properties or suitability for a specific use can not be derived from our statements. Possibly existing laws and regulations concerning the handling and use of our products have to be observed by the receiver of our products himself.





1/2

Technical Data Sheet

Divinol Syntholight Top 5W40

Viscosity/40°C / ASTM D 7042 : 86 mm²/s

Viscosity/100°C / ASTM D 7042 : 14.9 mm²/s

Viscosity index / ASTM D 2270 : 172

Density/15°C / DIN EN ISO 12185: 0,851 g/cm³

Pour point / DIN ISO 3016: < -30 °C

Flash point (Cleveland) / DIN ISO 2592: 230 °C

TBN: > 10 mgKOH/g

Application

Divinol Syntholight Top 5W40 is designed for spark ignition and diesel engines with or without turbo charger.

49430 04/2017-49430-10

The statements made in this publication are according to our present knowledge. They do not absolve the user from own examinations. A legally binding assurance of certain properties or suitability for a specific use can not be derived from our statements. Possibly existing laws and regulations concerning the handling and use of our products have to be observed by the receiver of our products himself.



