

# Technical Data Sheet

## Divinol Spezial 2000 HD 40

---

### Product description

Divinol Spezial 2000 HD 40 has high reserve capacities against wear and sludge. The product offers optimal lubrication, even under difficult conditions as well as a very high oxidation stability.

### Specification

API SG/CF

### Manufacturer performance

MB-Approval 227.0/228.0; MAN 270; MTU Type 1; Cat TO-2

Divinol Recommendation: ACEA E1/E2

### Characteristics

SAE Grade:	40
Ash / Sulfate DIN 51575:	0.8 %
Colour / DIN ISO 2049:	3,5
Viscosity/100°C / ASTM D 7042 :	13 mm <sup>2</sup> /s
Viscosity index / ASTM D 2270 :	145
Density/15°C / DIN EN ISO 12185:	0,871 g/cm <sup>3</sup>
Pour point / DIN ISO 3016:	- 33°C
Flash point (Cleveland) / DIN ISO 2592:	220°C
TBN:	6.5 mgKOH/g

### Application

All purpose HD single grade engine oil for Otto and Diesel engines and stationary motors. The mix of proven base oils with additives ensures effective wear and corrosion protection. Also suitable as hydraulic medium for machines  
49440 04/2017-49440-4

The statements made in this publication are according to our present knowledge. They do not absolve the user from own examinations. A legally binding assurance of certain properties or suitability for a specific use can not be derived from our statements. Possibly existing laws and regulations concerning the handling and use of our products have to be observed by the receiver of our products himself.

1 / 2

# Technical Data Sheet

## Divinol Spezial 2000 HD 40

---

and vehicles when matching OEM's specifications.

49440

04/2017-49440-4

The statements made in this publication are according to our present knowledge. They do not absolve the user from own examinations. A legally binding assurance of certain properties or suitability for a specific use can not be derived from our statements. Possibly existing laws and regulations concerning the handling and use of our products have to be observed by the receiver of our products himself.

2 / 2