

Technical Data Sheet

Divinol Syntholight 5W-40

Product description

Divinol Syntholight 5W-40 is a smooth running engine oil based on the most modern HC synthesis technology. This product guarantees excellent running properties, low abrasion and measurable fuel savings due to the reduction of friction and a fine cold starting performance. Divinol Syntholight 5W-40 has a high resistance against oxidation and the well balanced additive system avoids sludge.

Specification

API SN/CF; ACEA A3/B4

Manufacturer approval

MB-Approval 229.3

Manufacturer performance

BMW Longlife-01; MB-Approval 229.1; Porsche A40; PSA B71 2294/2296; Renault RN 0700/0710; VW 502.00/505.00; FIAT 9.55535 N2; GM-LL-B-025

Characteristics

SAE Grade:	5W40
Ash / Sulfate DIN 51575:	0.9 %
Colour / DIN ISO 2049:	4.5
Viscosity/40°C / ASTM D 7042 :	87 mm ² /s
Viscosity/100°C / ASTM D 7042 :	14.3 mm ² /s
Viscosity index / ASTM D 2270 :	172
Density/15°C / DIN EN ISO 12185:	0,850 g/cm ³
Pour point / DIN ISO 3016:	-39 °C

49520

05/2017-49520-10

The statements made in this publication are according to our present knowledge. They do not absolve the user from own examinations. A legally binding assurance of certain properties or suitability for a specific use can not be derived from our statements. Possibly existing laws and regulations concerning the handling and use of our products have to be observed by the receiver of our products himself.

1 / 2

Technical Data Sheet

Divinol Syntholight 5W-40

Flash point (Cleveland) / DIN ISO 2592:	≥ 200 °C
TBN:	10.8 mgKOH/g

Application

Divinol Syntholight 5W-40 is designed for spark ignition and diesel engines with or without turbo charger.

49520

05/2017-49520-10

The statements made in this publication are according to our present knowledge. They do not absolve the user from own examinations. A legally binding assurance of certain properties or suitability for a specific use can not be derived from our statements. Possibly existing laws and regulations concerning the handling and use of our products have to be observed by the receiver of our products himself.

2 / 2