

Technical Data Sheet

Divinol Syntholight 0W40

Product description

A fully synthetic, top-class engine oil with fuel-saving qualities for the most demanding Otto and Diesel car engines. Its unique viscosity range ensures excellent lubrications, even under extreme operating conditions and traffic situations. Due to the use of the best synthetic oils, this Divinol product has an excellent thermal stability and resistance to ageing and oxidation.

Advantages:

- optimum engine cleanliness
- very good wear protection
- no tearing of lubrication film
- hardly any evaporation losses

Specification

API SN/CF; ACEA A3/B4

Manufacturer approval

MB-Approval 229.5; BMW Longlife-01

Manufacturer performance

MB-Approval 229.3; VW 505.00/502.00; Porsche A40; Renault RN 0700/0710; Opel GM-LL-A-025; Opel GM-LL-B-025

Characteristics

SAE Grade:	0W40
Ash / Sulfate DIN 51575:	1 %
Viscosity/40°C / ASTM D 7042 :	75 mm ² /s
Viscosity/100°C / ASTM D 7042 :	13.3 mm ² /s

49530

05/2017-49530-14

The statements made in this publication are according to our present knowledge. They do not absolve the user from own examinations. A legally binding assurance of certain properties or suitability for a specific use can not be derived from our statements. Possibly existing laws and regulations concerning the handling and use of our products have to be observed by the receiver of our products himself.

1 / 2

Technical Data Sheet

Divinol Syntholight 0W40

Viscosity index / ASTM D 2270 :	182
Density/15°C / DIN EN ISO 12185:	0,845 g/cm ³
Pour point / DIN ISO 3016:	-42 °C
Flash point (Cleveland) / DIN ISO 2592:	222 °C
TBN:	10.2 mgKOH/g

Application

Can be used in gasoline and diesel engines with and without turbocharging, e.g. in passenger cars , vans and minibuses. The product is ideally fitting for vehicles equipped with exhaust aftertreatment systems. Additionally Divinol Syntholight 0W40 can cause fuel savings on short distances and in stop-and-go traffic.

49530

05/2017-49530-14

The statements made in this publication are according to our present knowledge. They do not absolve the user from own examinations. A legally binding assurance of certain properties or suitability for a specific use can not be derived from our statements. Possibly existing laws and regulations concerning the handling and use of our products have to be observed by the receiver of our products himself.

2 / 2