

Technical Data Sheet

Divinol Syntholight 505.01 SAE 5W-40

Product description

Divinol Syntholight 505.01 SAE 5W-40 is a synthetic smooth-running engine oil especially formulated for the requirements of VW Group-TDI engines. Benefits are:

- low fuel consumption
- lower thermal stress of the engine oil
- better cleaning characteristics
- lower engine wear

Divinol Syntholight 505.01 SAE 5W-40 is also suitable for LPG/CNG motors. According to the manufacturer's instructions!

Specification

API SN/CF; ACEA C3-12

Manufacturer approval

VW 502.00 / 505.00 / 505.01; MB Approval 229.51; BMW-Longlife 04

Manufacturer performance

Ford WSS M2C-917-A; Fiat 9.55535-S2; Porsche A40

Characteristics

SAE Grade:	5W-40
Viscosity/40°C / ASTM D 7042 :	75 mm ² /s
Viscosity/100°C / ASTM D 7042 :	13 mm ² /s
Viscosity index / ASTM D 2270 :	> 160
Density/15°C / DIN EN ISO 12185:	0,850 g/cm ³
Pour point / DIN ISO 3016:	< -30 °C
49540	

04/2017-49540-9

The statements made in this publication are according to our present knowledge. They do not absolve the user from own examinations. A legally binding assurance of certain properties or suitability for a specific use can not be derived from our statements. Possibly existing laws and regulations concerning the handling and use of our products have to be observed by the receiver of our products himself.

1 / 2

Technical Data Sheet

Divinol Syntholight 505.01 SAE 5W-40

Flash point (Cleveland) / DIN ISO 2592:

> 200 °C

Application

All cars with otto or diesel engines, including turbo-supercharger.

49540

04/2017-49540-9

The statements made in this publication are according to our present knowledge. They do not absolve the user from own examinations. A legally binding assurance of certain properties or suitability for a specific use can not be derived from our statements. Possibly existing laws and regulations concerning the handling and use of our products have to be observed by the receiver of our products himself.

2 / 2