

# Technical Data Sheet

## Divinol Multilight Racer 10W-40

---

### Product description

Divinol Multilight Racer 10W-40 is a modern, partly synthetic multipurpose engine especially for motorbikes or quads oil which reduces sludge due to special hydrocrack-raffinates. High alkaline reserves guarantee good corrosion protection. The new formulation saves fuel and reduces oil consumption. A multipurpose oil for every season.

### Specification

API SL/CF; ACEA A3/B3; JASO MA 2

### Manufacturer performance

VW 501.01/505.00; MB-Approval 229.1

### Characteristics

SAE Grade:	10W-40
Appearance:	brown, clear
Viscosity/40°C / ASTM D 7042 :	100 mm <sup>2</sup> /s
Viscosity/100°C / ASTM D 7042 :	15 mm <sup>2</sup> /s
Viscosity index / ASTM D 2270 :	≥ 160
Density/15°C / DIN EN ISO 12185:	0,862 g/cm <sup>3</sup>
Pour point / DIN ISO 3016:	≤ -30 °C
Flash point (Cleveland) / DIN ISO 2592:	240 °C
TBN:	7.8 mgKOH/g

### Application

Multi-purpose motor oil for motorbikes or quads.

49550

05/2017-49550-8

The statements made in this publication are according to our present knowledge. They do not absolve the user from own examinations. A legally binding assurance of certain properties or suitability for a specific use can not be derived from our statements. Possibly existing laws and regulations concerning the handling and use of our products have to be observed by the receiver of our products himself.

1 / 2

# Technical Data Sheet

## Divinol Multilight Racer 10W-40

---

49550

05/2017-49550-8

The statements made in this publication are according to our present knowledge. They do not absolve the user from own examinations. A legally binding assurance of certain properties or suitability for a specific use can not be derived from our statements. Possibly existing laws and regulations concerning the handling and use of our products have to be observed by the receiver of our products himself.

2 / 2