

Technical Data Sheet

Divinol Multilight 10W-40

Product description

Divinol Multilight 10W-40 is a modern, partly synthetic multipurpose engine oil which reduces sludge due to special hydrocrack-raffinates. High alkaline reserves guarantee good corrosion protection. The new formulation saves fuel and reduces the oil consumption. Also suitable for motorbikes according to standard JASO MA. A multipurpose oil for every season. Also suitable for LPG/CNG motors. According to the manufacturer's instructions!

Specification

API SN/CF; ACEA A3/B3; JASO MA

Approval

MB-Approval 229.1

Manufacturer performance

VW 505.00/502.00; PSA B71 2294; RN 0700; suitable for LPG/CNG motors according to manufacturer's instructions

Divinol Recommendation: MB- Approval 229.3

Characteristics

SAE Grade:	10W-40
Ash / Sulfate DIN 51575:	1.2 %
Colour / DIN ISO 2049:	3,5
Viscosity/40°C / ASTM D 7042 :	88 mm ² /s
Viscosity/100°C / ASTM D 7042 :	13 mm ² /s
Viscosity index / ASTM D 2270 :	150
Density/15°C / DIN EN ISO 12185:	0,868 g/cm ³

49610

05/2017-49610-23

The statements made in this publication are according to our present knowledge. They do not absolve the user from own examinations. A legally binding assurance of certain properties or suitability for a specific use can not be derived from our statements. Possibly existing laws and regulations concerning the handling and use of our products have to be observed by the receiver of our products himself.

1 / 2

Technical Data Sheet

Divinol Multilight 10W-40

Pour point / DIN ISO 3016:	-35 °C
Flash point (Cleveland) / DIN ISO 2592:	220 °C
TBN:	9 mgKOH/g

Application

Multi-purpose motor oil for all Otto and Diesel engines with or without turbo charger.

49610

05/2017-49610-23

The statements made in this publication are according to our present knowledge. They do not absolve the user from own examinations. A legally binding assurance of certain properties or suitability for a specific use can not be derived from our statements. Possibly existing laws and regulations concerning the handling and use of our products have to be observed by the receiver of our products himself.

2 / 2