

# Technical Data Sheet

## Divinol Super 15W-40

---

### Product description

Multigrade oil with ideal viscosity-temperature behaviour. The product has excellent cleaning and sludge carrying as well as dispersant and detergent properties. Also suitable for LPG/CNG motors according to manufacturer's instructions!

### Specification

API SJ/CF

### Manufacturer performance

MAN 271; MB-Approval 228.1; MTU Type 1

**Divinol recommendation:** ACEA A2-96/B2-98/E2-96

### Characteristics

SAE Grade:	15W40
Ash / Sulfate DIN 51575:	0.8 %
Colour / DIN ISO 2049:	3,5
Viscosity/100°C / ASTM D 7042 :	13 mm <sup>2</sup> /s
Viscosity index / ASTM D 2270 :	145
Density/15°C / DIN EN ISO 12185:	0,871 g/cm <sup>3</sup>
Pour point / DIN ISO 3016:	- 33°C
Flash point (Cleveland) / DIN ISO 2592:	220°C
TBN:	6.5 mgKOH/g

49623

04/2017-49623-3

The statements made in this publication are according to our present knowledge. They do not absolve the user from own examinations. A legally binding assurance of certain properties or suitability for a specific use can not be derived from our statements. Possibly existing laws and regulations concerning the handling and use of our products have to be observed by the receiver of our products himself.

1 / 2

# Technical Data Sheet

## Divinol Super 15W-40

---

### Application

HD-multigrade engine oil for otto and diesel engines.

49623

04/2017-49623-3

The statements made in this publication are according to our present knowledge. They do not absolve the user from own examinations. A legally binding assurance of certain properties or suitability for a specific use can not be derived from our statements. Possibly existing laws and regulations concerning the handling and use of our products have to be observed by the receiver of our products himself.

2 / 2