

Technical Data Sheet

Divinol Super 10W40

Product description

Multigrade engine oil, which is characterized by an optimal viscosity-temperature behavior and an excellent cleaning as well as mud carrying capacity due to optimal additivation of Divinol Super 10W40.

Specification

API SL/CF/CF-4; Jaso MA

Manufacturer performance

VW 505.00/501.01; MB-Freigabe 228.1; Volvo VDS; MAN 271

Divinol recommendation: ACEA A3-98/B4-98/E2-98

Characteristics

SAE Grade:	10W40
Viscosity/40°C / ASTM D 7042 :	84 mm ² /s
Viscosity/100°C / ASTM D 7042 :	12.7 mm ² /s
Viscosity index / ASTM D 2270 :	149
Density/15°C / DIN EN ISO 12185:	0,865 g/cm ³
Pour point / DIN ISO 3016:	-33 °C
Flash point (Cleveland) / DIN ISO 2592:	>240 °C
TBN:	9 mgKOH/g

Application

HD multi-grade engine oil for superior performance in gasoline and diesel engines.

49625

04/2017-49625-5

The statements made in this publication are according to our present knowledge. They do not absolve the user from own examinations. A legally binding assurance of certain properties or suitability for a specific use can not be derived from our statements. Possibly existing laws and regulations concerning the handling and use of our products have to be observed by the receiver of our products himself.

1 / 2

Technical Data Sheet

Divinol Super 10W40

49625

04/2017-49625-5

The statements made in this publication are according to our present knowledge. They do not absolve the user from own examinations. A legally binding assurance of certain properties or suitability for a specific use can not be derived from our statements. Possibly existing laws and regulations concerning the handling and use of our products have to be observed by the receiver of our products himself.

2 / 2