

Technical Data Sheet

Divinol Super Turbo 20W-50

Product description

Divinol Super Turbo 20W-50 is a multi-purpose engine oil of high quality for every season. The optimal additive formulation ensures excellent engine lubrication during all operating conditions. Can be deployed in motorbikes according standard JASO MA.

Also suitable for LPG/CNG motors. According to the manufacturer's instructions!

Specification

API SJ/CF/CF-4; JASO MA; MIL-L-2104-E;

Manufacturer performance

VW 501.01 / 505.00; MB-Approval 228.1/229.1; MAN 271;Allison C-4; Caterpillar TO-2; Volvo VDS; Renault RGD

Divinol recommendation: ACEA A3-02/B3-98/E2-96

Characteristics

SAE Grade:	20W50
Viscosity/40°C / ASTM D 7042 :	165 mm ² /s
Viscosity/100°C / ASTM D 7042 :	19.1 mm ² /s
Viscosity index / ASTM D 2270 :	129
Density/15°C / DIN EN ISO 12185:	888 kg/m ³
Pour point / DIN ISO 3016:	< -15
Flash point (Cleveland) / DIN ISO 2592:	>208 °C

Application

Multi-purpose motor oil for all otto and diesel engines including turbo-supercharger.

49632

04/2017-49632-7

The statements made in this publication are according to our present knowledge. They do not absolve the user from own examinations. A legally binding assurance of certain properties or suitability for a specific use can not be derived from our statements. Possibly existing laws and regulations concerning the handling and use of our products have to be observed by the receiver of our products himself.

1 / 2

Technical Data Sheet

Divinol Super Turbo 20W-50

49632

04/2017-49632-7

The statements made in this publication are according to our present knowledge. They do not absolve the user from own examinations. A legally binding assurance of certain properties or suitability for a specific use can not be derived from our statements. Possibly existing laws and regulations concerning the handling and use of our products have to be observed by the receiver of our products himself.

2 / 2