

Technical Data Sheet

Divinol DSG Fluid

Product description

Divinol DSG Fluid is a dual clutch transmission fluid, which can be used in vehicles that require DCTF oils. The product can be used for the VW group vehicles with DCTF gearboxes from year 2003. Further applications are in Ford, Volvo, Chrysler, Peugeot, Citroen and Mitsubishi 6-speed DCTF driven cars from year 2007.

Divinol DSG Fluid offers the following advantages:

- longer, smooth shifting through improved friction characteristics
- improved load carrying capacity and therefore extended gear life
- better seal compatibility and therefore better gear and environmental protection
- Divinol DSG Fluid can be used to reduce variety of oils

Specification

Dual Clutch Transmission Oil

Manufacturer performance

MB-Approval 236.21; VW G 052 182; VW G 052 529; VW DSG DQ 200; Ford WSS-M2C936-A; Ford WSD-M2C 200-D2; Ford 1490763; Ford 1490761; Fiat 955550-MZ6; Chrysler 68044345; Volvo 1161838; Volvo 1161839; Peugeot/ Citroen 9734.S2; Mitsubishi MZ320065 Dia-Queen SSTF-I; Porsche Oil No. 999.917.080.00; BMW 83 22 2 148 578; BMW 83 22 2 148 579; BMW 83 22 0 440 214; BMW 83 22 2 147 477; BOT 341; Renault EDC

Characteristics

Appearance:	yellowish, clear
Viscosity/40°C / ASTM D 7042 :	35 mm ² /s
Viscosity/100°C / ASTM D 7042 :	7.2 mm ² /s
Viscosity index / ASTM D 2270 :	175
Density/15°C / DIN EN ISO 12185:	0,855 g/cm ³
Pour point / DIN ISO 3016:	< -40°C
Flash point (Cleveland) / DIN ISO 2592:	≥ 180 °C

51790

04/2017-51790-6

The statements made in this publication are according to our present knowledge. They do not absolve the user from own examinations. A legally binding assurance of certain properties or suitability for a specific use can not be derived from our statements. Possibly existing laws and regulations concerning the handling and use of our products have to be observed by the receiver of our products himself.

1 / 2

Technical Data Sheet

Divinol DSG Fluid

Application

Divinol DSG Fluid is suitable as Dual Clutch Transmission Oil in cars. Divinol DSG Fluid can be deployed according to manufacturers' specifications.

51790

04/2017-51790-6

The statements made in this publication are according to our present knowledge. They do not absolve the user from own examinations. A legally binding assurance of certain properties or suitability for a specific use can not be derived from our statements. Possibly existing laws and regulations concerning the handling and use of our products have to be observed by the receiver of our products himself.

2 / 2