

Technical Data Sheet

Divinol ATF Premium VI

Product description

Divinol ATF Premium VI is a red colored power transmission oil for automatic transmissions and offers following characteristics:

- Superior oxidation stability
- Very good anti wear characteristics
- Premium cold flow properties
- Broadly temperature range deployment
- Not aggressive to any sort of seal
- Very good shear stability
- Suitable for prolonged oil drain intervals
- Universal deployable ATF

Specification

GM Dexron VI*; GM Dexron III G/H; GM Dexron II D; GM Dexron TASA; Ford Mercon V; JASO 1 A

Manufacturer performance

MB-Approvals 236.3/ 236.5 / 236.6 /236.7 / 236.8 / 236.9 / 236.91/ 236.10 / 236.11; VW G 052 025 / G 052 162 / G 052 990 / G 055 025 / G US 000 162; BMW / MINI P/N 81 22 9 400 272/275; BMW / MINI P/N 81 22 9 407 858/859; BMW / MINI P/N 83 22 0 024 359, BMW / MINI P/N 83 22 0 026 922, BMW / MINI P/N 83 22 0 402 413, BMW / MINI P/N 83 22 0 403 248, BMW / MINI P/N 83 22 0 403 249, BMW / MINI P/N 83 22 7 542 290, BMW / MINI P/N 83 22 9 407 765, BMW / MINI P/N 83 22 9 407 807; Porsche P/N 000 043 204 41, Porsche P/N 000 043 204 41, Porsche P/N 000 043 205 28, Porsche P/N 999 917 547 00; PSA Peugeot Citroën P/N Z 000169756; Renault Matic D2; Hyundai/Kia SP II / III; Mazda ATF M III, Mazda Type T-IV; Mitsubishi ATF-J2, Mitsubishi SP, P/N MS991156, Mitsubishi SP-II, Mitsubishi SP-III; Nissan / Infinity N402, Matic D/J/K/S; Subaru ATF HP, Subaru P/N K0140Y0700; Volvo 97341, Volvo P/N 1161529, Volvo P/N 1161540 / 1161640, Volvo VCE 1273.41; Chrysler ATF +3/4; Honda ATF- Z1; Hyundai SP-II / III / SPH- IV / NWS 9638; Suzuki 3314, Suzuki 3317; Aisin Warner AW-1, JWS 3309, JWS 332; Saab 93 165 147; Voith 55.6335.XX (G607); Isuzu ATF III, Isuzu P/N 08200-9001; Bentley JNV 862 564 D; SSANG YONG DSIH 5M-66; Jaguar JLM 20238, Jaguar JLM 21044, Jaguar K17, Jaguar WSS-M2C922-A1; ZF TE ML- 03D,05L,09,11A,11B,14A,14C,17C,21L; Allison C4 / TES 295 / TES 389

*Viscosity requirements not met

51810

04/2017-51810-21

The statements made in this publication are according to our present knowledge. They do not absolve the user from own examinations. A legally binding assurance of certain properties or suitability for a specific use can not be derived from our statements. Possibly existing laws and regulations concerning the handling and use of our products have to be observed by the receiver of our products himself.

1 / 2

Technical Data Sheet

Divinol ATF Premium VI

Characteristics

Appearance:	Red
Viscosity/40°C / ASTM D 7042 :	35 mm ² /s
Viscosity/100°C / ASTM D 7042 :	6.6 mm ² /s
Viscosity index / ASTM D 2270 :	150
Density/15°C / DIN EN ISO 12185:	850 kg/m ³
Pour point / DIN ISO 3016:	≤ -39 °C
Flash point (Cleveland) / DIN ISO 2592:	≥ 200 °C

Application

Divinol ATF Premium VI is suitable as transmission oil in automatic transmissions of cars, trucks, busses and special vehicles. Also possible for hydrodynamic converters, hydraulics and servo-steerings in accordance to manufacturers` specifications.

51810

04/2017-51810-21

The statements made in this publication are according to our present knowledge. They do not absolve the user from own examinations. A legally binding assurance of certain properties or suitability for a specific use can not be derived from our statements. Possibly existing laws and regulations concerning the handling and use of our products have to be observed by the receiver of our products himself.

2 / 2