

Technical Data Sheet

Divinol Hypoid-Getriebeöl 85W-140

Product description

Multigrade hypoid gear oil with high oxidation stability. Its EP-additives offer a stable oil film and reduce abrasion even under highest loading of the tooth profiles and high slide share.

Specification

API GL 5; MIL-L-2105 D

Manufacturer performance

MAN 342 M1; MB-Approval 235.0; Renault GL-5; Voith 3.325-339; Volvo 97310 / 97316; ZF TE-ML 07A, 08, 16B/C/D, 17B, 19B, 21A

Characteristics

Colour / DIN ISO 2049:	L 5,0
Viscosity index / ASTM D 2270 :	94
Viscosity/40°C / ASTM D 7042 :	340 mm ² /s
Viscosity/100°C / ASTM D 7042 :	28 mm ² /s
Density/15°C / DIN EN ISO 12185:	0,905 g/cm ³
Pour point / DIN ISO 3016:	≤ -19 °C
Flash point (Cleveland) / DIN ISO 2592:	≥ 200 °C

Application

Used mainly for heavy loaded hypoid gear with extreme operating conditions. An ideal gear oil for differential and equalizing gears in rear axles.

51980

04/2017-51980-14

The statements made in this publication are according to our present knowledge. They do not absolve the user from own examinations. A legally binding assurance of certain properties or suitability for a specific use can not be derived from our statements. Possibly existing laws and regulations concerning the handling and use of our products have to be observed by the receiver of our products himself.

1 / 1