

Technical Data Sheet

Divinol Synthogear Extra LS 75W-90

Product description

Divinol Synthogear Extra LS 75W-90 is a high-performance LS oil, multifunctional gearbox oil for the rear axles and final drives of passenger cars and for certain vehicles gearboxes. This product has an unusually wide operating temperature range.

- optimum viscosity–temperature behaviour
- high wear protection
- excellent oxidation stability

Specification

API GL 4 / 5 LS; MIL-L 2105D/PRF-2105E

Manufacturer performance

MAN 341 E2; MAN 341 Z2; MAN 342 M2; Arvin Meritor 0-76-N; DAF; Iveco; MB-Approval 235.0; Mack GO-J; Scania STO 1:0; JCB-Standard 4000/3900; ZF TE ML 02B/05A/07A/08/12L/12M/16B/16C/16D/17B/19B/21A

Characteristics

SAE Grade:	75W-90
Appearance:	clear
Colour / DIN ISO 2049:	< 2.0
Viscosity/40°C / ASTM D 7042 :	110 mm ² /s
Viscosity/100°C / ASTM D 7042 :	15 mm ² /s
Viscosity index / ASTM D 2270 :	> 140
Density/15°C / DIN EN ISO 12185:	0.880 g/cm ³
Pour point / DIN ISO 3016:	< -40 °C
Flash point (Cleveland) / DIN ISO 2592:	> 170 °C

52000

04/2017-52000-19

The statements made in this publication are according to our present knowledge. They do not absolve the user from own examinations. A legally binding assurance of certain properties or suitability for a specific use can not be derived from our statements. Possibly existing laws and regulations concerning the handling and use of our products have to be observed by the receiver of our products himself.

1 / 2

Technical Data Sheet

Divinol Synthogear Extra LS 75W-90

Application

Divinol Synthogear Extra LS 75W-90 is e.g. for rear axles and final drives of commercial & private vehicles and certain gearboxes.

52000

04/2017-52000-19

The statements made in this publication are according to our present knowledge. They do not absolve the user from own examinations. A legally binding assurance of certain properties or suitability for a specific use can not be derived from our statements. Possibly existing laws and regulations concerning the handling and use of our products have to be observed by the receiver of our products himself.

2 / 2