Technical Data Sheet

Divinol Profi Lube SL

Product description

Divinol Profi Lube SL is a transparent special lubricant for the universal use in industry, craft as well as for hobby and bicycles. Due to the spraying unit, the grease can be applied exactly, economically and without problems even on parts which are difficult to reach.

Advantages :

- · wear of chains is reduced considerably
- strong adhesion even for higher speed of the chains
- · optimum corrosion protection of the parts even for permanent contact with salt water
- · pressure resistant lubrication film for economical consumption

Characteristics	
Operating temperature range:	-30 - 110 C
Density / 50°C:	640 kg/m³
Composition:	water repellent grease dissolved in aerosol

Application

Divinol Profi Lube SL is a special lubricant based on synthetic oils for the universal use, e. g. for chains, bowden cables, open ropes, rolls and friction marks, which have to bear high shock loads, vibrations and/or strong atmospheric exposures.

Do not spary on hot surfaces!

62301 LK

04/2017-62301 LK-5

The statements made in this publication are according to our present knowledge. They do not absolve the user from own examinations. A legally binding assurance of certain properties or suitability for a specific use can not be derived from our statements. Possibly existing laws and regulations concerning the handling and use of our products have to be observed by the receiver of our products himself.

1/1



ZG Division: Divinol Lubricants & Release Agents Zeller+Gmelin GmbH & Co. KG Schlossstr. 20 - 73054 Eislingen/Fils Tel. +49 7161 802-0 - Fax +49 7161 802-230 www.zeller-gmelin.de - dst@zeller-gmelin.de

