

# Technical Data Sheet

## Divinol Mehrzweck-Getriebeöl SAE 80

---

### Product description

High performance gear oil according API GL-4.

### Specification

API GL 4

### Manufacturer performance

MAN 341 E1; MB-Approval 235.1; ZF TE-ML 06L, 08, 16A, 17A, 19A, 19C

### Characteristics

SAE Grade:	80W
Colour / DIN ISO 2049:	L 3,0
Viscosity/40°C / ASTM D 7042 :	85 mm <sup>2</sup> /s
Viscosity/100°C / ASTM D 7042 :	8.5 mm <sup>2</sup> /s
Viscosity index / ASTM D 2270 :	110
Density/15°C / DIN EN ISO 12185:	0,880 g/cm <sup>3</sup>
Pour point / DIN ISO 3016:	-25°C
Flash point (Cleveland) / DIN ISO 2592:	220 °C

### Application

A high-performance, multi-purpose transmission oil for vehicle gearboxes, heavily loaded final drives and transaxle drives.

80700

04/2017-80700-7

The statements made in this publication are according to our present knowledge. They do not absolve the user from own examinations. A legally binding assurance of certain properties or suitability for a specific use can not be derived from our statements. Possibly existing laws and regulations concerning the handling and use of our products have to be observed by the receiver of our products himself.

1 / 1