

# Technical Data Sheet

## Divinol Mehrzweck-Getriebeöl 85W-90

---

### Product description

High performance gear oil according API GL-4.

### Specification

API GL 4

### Manufacturer performance

MAN 341 E1; MB-Approval 235.1; ZF TE-ML 06L, 08, 16A, 17A, 19A, 19C

### Characteristics

SAE Grade:	85W-90
Colour / DIN ISO 2049:	L 3,0
Viscosity/40°C / ASTM D 7042 :	190 mm <sup>2</sup> /s
Viscosity/100°C / ASTM D 7042 :	14.5 mm <sup>2</sup> /s
Viscosity index / ASTM D 2270 :	110
Density/15°C / DIN EN ISO 12185:	885 kg/m <sup>3</sup>
Pour point / DIN ISO 3016:	-25 °C
FZG-test A/8,3/90 - Damage loading step / DIN 51 354:	> 12

### Application

A high-performance, multi-purpose transmission oil for vehicle gearboxes and lightly loaded final drives, where API GL-4 can be filled.

80714

04/2017-80714-7

The statements made in this publication are according to our present knowledge. They do not absolve the user from own examinations. A legally binding assurance of certain properties or suitability for a specific use can not be derived from our statements. Possibly existing laws and regulations concerning the handling and use of our products have to be observed by the receiver of our products himself.

1 / 1